



Security Striking Plates 1487-1 – 1487-5, 1487-9

Application

For perimeter protection and other important doors, where security is of essence.

Features

- Meets the requirements of the EN 12209 security grade 3
- Mounted with high security screws to resist higher break force and for maximum resistance to attack.

Function

- For protection of the lock case dead bolt from physical attack and manipulation.
- With edge rolled front for low friction between striking plate and the latch.
Ex. 1487-1 – 1487-4 have adjustable lips in the security box to get the right border pressure.



| | Width | Lip | Angle | Length |
|--------|-------|------|-------|--------|
| 1487-1 | 40 | 13,5 | | 200 |
| 1487-2 | 40 | 16,5 | | 200 |
| 1487-3 | 43,5 | 20 | | 200 |
| 1487-4 | 45 | 21,5 | | 200 |
| 1487-5 | 29,5 | 5,5 | 29,5 | 200 |
| 1487-9 | 25 | 5,5 | | 245 |

Standard Striking Plates 1264-1 – 1264-8

Application

For interior doors and accomodation where standard locking is required.

Features

- For limited break force
- Rounded leading edge for low friction between the striking plate and latch bolt

Function

- Keep the door in closed position through the latch bolt/dead bolt engagement
- 1264-1 – 1264-7 with single adjusting lip for adjustment of border pressure



| | Width | Lip | Angle | Length |
|--------|-------|------|-------|--------|
| 1264-1 | 36 | 13,5 | | 150 |
| 1264-2 | 36 | 16 | | 150 |
| 1264-3 | 36 | 19 | | 150 |
| 1264-4 | 40 | 23 | | 150 |
| 1264-5 | 36 | 13 | | 150 |
| 1264-6 | 36 | 16 | | 150 |
| 1264-7 | 40 | 20 | | 150 |
| 1264-8 | 24 | 5,5 | 22 | 155 |



1887-1

1887-5

1888-1



1888-5

1887-9

1887-1 – 1887-5, 1887-9, 1824-1 – 1824-7, 1888-1, 1888-5

Application

For perimeter protection and other important doors, where security is of essence.


Features

- Meets the requirements of the EN 12209 security grade 3
- Mounted with high security screws to resist higher break force and for maximum resistance to attack.

Function

- With edge rolled front for low friction between striking plate and the latch
Ex. 1887-1 – 1887-4 have adjustable lips in the security box to get the right border pressure
- Plane security striking plates 1887-1 1887-5 for modular locks has adjustable screws to eliminate elasticity in the frame.
- Plane security striking plates 1887-1 1887-4 can be complemented with tin plate 1895 for alternative lip width.
- 1887-1 – 1887-4 can be complemented with deadlocking bar 1893 for locks with deadlocking latch.

| | Width | Lip | Angle | Length |
|--------|-------|------|-------|--------|
| 1824-1 | 32 | 5,5 | 8 | 225 |
| 1824-2 | 32 | 5,5 | 25 | 225 |
| 1824-3 | 32 | 7,5 | 27 | 225 |
| 1824-4 | 32 | 7,5 | 15 | 225 |
| 1824-5 | 40 | 14 | 8 | 225 |
| 1824-6 | 32 | 5,5 | 15 | 225 |
| 1824-7 | 32 | 5,5 | 20 | 225 |
| 1887-1 | 40 | 12,5 | | 200 |
| 1887-2 | 40 | 15,5 | | 200 |
| 1887-3 | 43,5 | 19 | | 200 |
| 1887-4 | 45 | 20,5 | | 200 |
| 1887-5 | 29,5 | 4,5 | 29,5 | 200 |
| 1888-1 | 30 | 7 | | 150 |
| 1888-5 | 29 | 6 | 27 | 150 |
| 1887-9 | 25 | 5.5 | | 245 |



2800, 2860, 2861, 2862, 2863, 2864, 2865, 2866, 2876, 2885, 2887, 2888, 2892

Application

For interior doors and accomodation where standard locking is required.

Features

- For limited break force
- Rounded leading edge for low friction between the striking plate and latch bolt

Function

- Keep the door in a closed position through the latch/dead bolt engagement
- 2864, 2865, 2860 and 2861 with single adjusting lip for adjustment of border pressure

| | Width | Lip | Angle | Length | Ri/Le |
|--------|-------|------|-------|--------|-------|
| 2860-1 | 35 | 15,5 | - | 155 | X |
| 2860-2 | 41,5 | 22 | - | 155 | X |
| 2860-5 | 24 | 3,5 | 22 | 155 | X |
| 2861 | 40 | 21 | - | 135 | |
| 2862-1 | 35 | 15 | - | 125 | |
| 2862-2 | 35 | 21,5 | - | 125 | |
| 2862-3 | 32,5 | 14,5 | - | 213 | |
| 2862-6 | | | | | |
| 2863-5 | 22 | 4 | 8 | 215 | |
| 2863-6 | 22 | 4 | 22 | 215 | |
| 2864-1 | 35 | 15 | - | 125 | |
| 2864-2 | 32,5 | 12,5 | - | 125 | |
| 2865-1 | 40 | 12,5 | - | 200 | |
| 2865-2 | 40 | 15,5 | - | 200 | |
| 2885 | 36 | 17,5 | - | 83 | |
| 2887-1 | 25 | - | - | 125 | |
| 2887-2 | 40 | - | - | 132 | |
| 2888 | 22 | - | - | 83 | |



2860-1



2861



2862-2



2863-5



2864



2865-1



2885



2887-1



2888



2866-1



2866-2

2866-1, 2866-2, 2876-1, 2876-5, 2892-5, 2892-6

Application

For interior doors and accomodation that don't require approved locking.

Features

- For limited break force
- Rounded leading edge for low friction between the striking plate and latch bolt

Function

Keep the door in a closed position with latch or dead bolt operation



2876-1 *



2876-5 *

| | Width | Lip | Angle | Length | Ri/Le |
|----------|-------|------|-------|--------|-------|
| 2866-1 | 33 | 14,5 | - | 127 | X |
| 2866-2 | 43 | 14,5 | - | 127 | |
| 2876-1 * | 60 | 9 | - | 70 | |
| 2876-5 * | 27,5 | 6 | 8 | 111 | |
| | | | | | |
| 2892-5 | 20 | 2 | 12,5 | 50 | |
| 2892-6 | 17 | | 6 | 50 | |

* = For rim lock 576 and 577



2892-5



2892-6

