

## Declaration of performance No. 18015-1

- 1. ID code of the product type:** Electric Lock
- 2. Type number:** EL581, EL590, EL595, EL596
- 3. Intended use:** On fire and smoke compartmentation doors  
For doors on escape routes
- 4. Manufacturer:** Abloy Oy  
Joensuu factory  
Wahlforssinkatu 20  
FI-80100 JOENSUU  
FINLAND
- 5. System or systems of assessment and verification of constancy of performance of the construction product:** AVCP 1
- 6. Notified product certification body:** Eurofins Expert Services Oy  
ID No: 0809  
Kivimiehentie 4  
FI-02150 ESPOO  
FINLAND
- CE Certificates:** No. 0809-CPR-1157  
No. 0809-CPR-1053

**7. Declared performance:**

Essential Characteristics	Grade	Performance	Harmonized technical specification
4.3 Category of use	<b>3</b>	Doors in public buildings	<b>EN 14846:2008</b>
4.4 Durability and load on latchbolt	<b>S</b>	200 000 test cycles, 50 N load on latchbolt	
4.5 Door mass and closing force	<b>5</b>	Up to 200 kg, closing force max. 25 N	
4.6 Suitability for use on fire/smoke doors	<b>F</b>	EI120 fire doors	
4.7 Safety	-	See EN179:2008	
4.8 Corrosion resistance, temperature and humidity	<b>L</b>	High resistance, -25 °C to +70 °C, Level 2	
4.9 Security	<b>3</b>	Medium security, no drill resistance	
4.10 Security – Electrical function	<b>1</b>	Indication	
4.11 Security – Electrical manipulation	<b>1</b>	Grade 1	
<b>Dangerous substances</b>	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

Essential Characteristics	Grade	Performance	Harmonized technical specification
7.1 Category of use	<b>3</b>	High frequency of use where there is little intensive to exercise care	<b>EN 179:2008</b>
7.2 Durability	<b>7</b>	200 000 test cycles	
7.3 Door mass	<b>6</b>	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	<b>B</b>	Suitable for use on smoke door assemblies based on a test in accordance with EN 1634-1	
7.5 Safety	<b>1</b>	All emergency exit devices have a critical safety function	
7.6 Corrosion resistance	<b>3</b>	96 h (high resistance)	
7.7 Security	<b>4</b>	3 000 N	
7.8 Projection of operating element	<b>2</b>	Projection up to 100 mm (standard projection)	
7.9 Type of operation	<b>A</b>	Emergency exit device with "lever handle" operation	
7.10 Field of door application	<b>B</b>	Outwardly opening single exit door only	
<b>Dangerous substances</b>	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2020-01-29  
On behalf of Abloy Oy




---

Jari Kervinen  
CTO